



ELECTRONIC MEMORY RECORDERS Hostile Environment Acquisition Tool

Spartek Systems specializes in providing the oil and gas industry with high quality data to monitor well performance and diagnose potential problems. Founded in 1994, Spartek Systems leads the industry in providing cost effective solutions for acquiring reliable well information.

Product Overview

The SS2110 Hostile Environment Acquisition Tool (HEAT) is a memory based instrument designed to acquire temperature and pressure data in the most challenging well environments. The HEAT records up to 2.7 million sample points of pressure and temperature. It is capable of operating in well temperatures to 350°C, and pressures to 20,000 psi. The HEAT has demonstrated superior operational performance in wells with temperatures greater than 300°C. The instrument utilizes a vacuum flask to insulate the internal electronics, pressure transducer and batteries from the high temperatures in the well-bore. A special tool housing made of Inconel-718 is employed to provide resistance to any corrosive chemicals present in the well.



The SparGauge software package controls the memory programming and the downloading of data from the tool. The software also facilitates the data presentation, so as to allow the user to quickly create gradient plots, pressure and temperature versus time plots, and many other reports with minimal effort. In addition, if combined with Spartek's Line Management System the pressure and temperature data can be presented in an API Log format to display pressure and temperature curve data versus well depth.

As an easy reference, the theoretical temperatures and time durations at which the HEAT will operate are 350°C (662°F) for 4 hours, 300°C (572°F) for 6 hours, and 200°C (392°F) up to 12 hours.

Primary Features

- ▶ 350°C maximum temperature for 4 hours
- ▶ 20,000 psi maximum pressure
- ▶ Sour Service Rated (Hostile environment)
- ▶ RTD Probe for Well Temperature Profiles
- ▶ Metal To Metal Seals
- ▶ USB for Fast Data Retrieval
- ▶ Easy Setup and Programming
- ▶ Rugged and Reliable
- ▶ Windows 11/10/8 Operating Systems

Applications

- ▶ Steam Injection Surveys
- ▶ Pressure Transient Surveys
- ▶ Enhanced Recovery Profiles
- ▶ Well Testing
- ▶ Monitor Well Performance
- ▶ Completion Diagnostics
- ▶ Well Stimulation
- ▶ Reservoir Characterization
- ▶ Gradient Surveys

SPARTEK SYSTEMS

Providing Our Customers With "Best In Class" Technology

Email: sales@sparteksystems.com

<http://www.sparteksystems.com>

Specifications:

MODEL	SS2110 SB
Pressure Sensor Type Range(s) (psi) Accuracy Resolution Drift	Sapphire 10000, 15000, 20000 0.05% Full-Scale 0.0003% Full-Scale < .03% Full-Scale / year
Temperature Sensor Type Range Accuracy Resolution Drift	External RTD Class one -20°C to 350°C / -4°F to 662°F 1.0°C / 1.8°F 0.001°C / 0.0018°F < 1.0°C / 1.8°F per year
Power Requirements Voltage (min) Current (Sleep) Current (Sample)	3 V 0.10 mA 4.50 mA
Data Acquisition Channels Fastest sample rate Memory Capacity Options	Pressure Pressure Sensor Temperature External Temperature Time 1 sample/second 2,700,000 samples 5,400,000 samples Pressure Trigger
Housing Material Diameter Make Up Length	17-4 PH / Inconel 718-NACE 1.69" 57.19 inches
Communications	USB / RS232
Surface Read Out	No
Software Compatibility	Windows 11/10/8

Specifications subject to change without notice

For More Information, Pricing, and Technical Support Contact:



#1 Thevenaz Industrial Trail
Sylvan Lake, Alberta
Canada, T4S 2J6

Tel: (403) 887-2443
Fax: (403) 887-4050

Providing Our Customers With "Best In Class" Technology